

HEAVY-DUTY BATTERY CHARGERS

LITHIUM-ION CHARGERS

NEW



| | |
|------------------|--|
| CATALOG NO. | 48-59-2801 |
| DESCRIPTION | V28™ ONE-HOUR Li-ion CHARGER Charges ALL Milwaukee V28 battery packs. |
| COMPATIBLE WITH: | All 28 Volt Milwaukee Batteries |

V28™ ONE-HOUR CHARGER 48-59-2801

- **High Visibility 360° LED** – Indicates charging status from across the room.
- **Rubberized Feet** – Keeps charger in place on slick surfaces.
- **Extended Sides**
 - Protect battery pack while on charger
 - Adds stability to prevent charger from tipping forward while pack is charging
- **Progressive Charge Indication** – Battery LED's light-up incrementally as the battery is charged. Provides quick feedback on current charge level of battery pack.
- **Pass-Through Plug** – Conserves valuable outlet space on the job site.
- **Encapsulated Circuit Board for Extreme Durability** – Protects electronics from debris, moisture, and impact.

Ni-Cd CHARGERS



| | |
|------------------|---|
| CATALOG NO. | 48-59-0255 |
| DESCRIPTION | ONE-HOUR Ni-Cd UNIVERSAL CHARGER Charges ALL Milwaukee "Slide-On Style" batteries. |
| COMPATIBLE WITH: | All 18, 14.4 and 12 Volt Milwaukee "Slide-On Style" batteries. |



| | |
|------------------|---|
| CATALOG NO. | 48-59-0186 |
| DESCRIPTION | ONE-HOUR Ni-Cd VEHICLE CHARGER Plugs into vehicle's cigarette lighter. |
| COMPATIBLE WITH: | Charges ALL Milwaukee "Slide-On Style" batteries. All 18, 14.4 and 12 Volt Milwaukee "Slide-On Style" batteries. |

ONE HOUR Ni-Cd AND Ni-MH CHARGERS

48-59-0255 AND 48-59-0186

- **Generator, Inverter And Long Extension Cord Ready - Due To Wide Input Voltage Range Of AC Charger**
- **Maximizing Battery Pack Life**
 - Allow Battery Pack To Cool Before Charging
 - Do Not Deeply Discharge Battery
 - Store Batteries In Cool Places
- **2-Step Charging Performance**
 - 1) 1 Hour Fast-Charge Mode
 - 2) Maintenance Mode - Keeps The Battery Pack Fully Charged While On Charger
- **Temperature Protection Circuitry**
 - Charge Between 40° To 105° F – Charges Battery Packs At A Slower Rate When Battery Pack Temperature Is Below 40°F Or Above 105°F
 - Automatically Switches To Fast Charge Mode When Battery Pack Temperature Falls Within 40°F to 105°F Temperature Range



| | |
|------------------|--|
| CATALOG NO. | 48-59-0260 |
| DESCRIPTION | MULTI-BAY Ni-Cd CHARGER Charges ALL Milwaukee "Slide-On Style" batteries. <i>See copy at right for more details!</i> |
| COMPATIBLE WITH: | All 18, 14.4 and 12 Volt Milwaukee "Slide-On Style" batteries. |



MULTI-BAY CHARGER 48-59-0260

- 1 Charge Up To Three Battery Packs Of The Same Or Other Voltage Simultaneously
 - 2 Charges In 45 Minutes For Minimal Down Time
 - 3 Micro-Controlled Conditioning Mode Maximizes Run Time Automatically During Each Charge Cycle
 - 4 Generator, Inverter And Long Extension Cord Ready - Due To Wide Input Voltage Range Of AC Charger
 - 5 Dust Cover Protects Charger Terminals From Job Site Contamination And Debris
 - 6 Dust Cover Automatically Retracts When A Battery Is Inserted
 - 7 9' Cord With Pass Through Plug
 - 8 High Visibility LED Indicators Let You Know What Charging Stage The Battery Pack Is In
 - 9 Convenient Cord Wrap Also Acts As A Shock Absorber If The Unit Is Tipped Or Dropped
- **Durable Construction Protects The Charger In Harsh Job Site Environment** – Impact resistant base provides ultimate protection in job site conditions.
 - **Withstands 8' Drop To Concrete** – (With battery packs attached.)